










260 TJ

TECHNICAL DATA SHEET



260 TJ

| | | 260 TJ | |
|--|---|----------------------------------|-----------|
|  | Working height | 25.91 m | |
| | Platform height | 23.91 m | |
| | Outreach | 19.70 m | |
|  | Jib tilting | +70°/-63° | |
| | Basket rotation | +90°/-90° | |
| Turret rotation | | 360° continuous | |
|  | Capacity | 400 kg (3 operators) | |
| | Basket (width and length) | 2.30 x 0.90 m | |
|  | D - Overall width | 2.43 m | |
| | A - Overall length | 10.8 m | |
| | C - Overall height | 2.75 m | |
| | A1 - Overall length when folded | 8 m | |
| | C1 - Overall height when folded | 2.75 m | |
| | H - Inside turning circle | 1.75 m | |
| | I - Outside turning circle | 6.84 m | |
| | L - Turning Radius (basket) | 9.27 m | |
| | E - Ground clearance | 43 cm | |
| | B - Wheelbase | 2.80 m | |
| |  | Speed of forward movement | 4.70 km/h |
| | | Working speed | 0.80 km/h |
| |  | Maximum slope accessible | 40 % |
| Maximum tilt | | 4° | |
|  | Types of tyres | Solid Tyres | |
| | Dimension of tyres | 20" | |
| | Driving wheels | 4 | |
| | Steering/directional wheels | 4 | |
|  | Weight | 16300 kg | |
| | <small>(varies according to options & standards of the country)</small> | | |
|  | Engine | KUBOTA V2403-M | |
| | Power | 45 cv / 33,6 kw | |
| | Fuel tank capacity | 72 L | |
| | Environmental noise (LwA) | 105 dB | |

Standard equipment

| |
|--|
| Jib |
| Oscillating front axle |
| Continuous Rotation |
| Wide high capacity basket |
| Proportional levers |
| 4 simultaneous movements |
| 4 wheel drive |
| 4 wheel steer |
| Wheels crab position |
| Mouvements X/Y (horizontaux, verticaux) |
| Electronic compensation of the basket |
| Solid Tyres |
| Differential Lock |
| Front Axle limited slip differential |
| Diagnostic and Maintenance fully integrated |
| Hour meter |
| Fuel gauge with low level warning |
| Tool box |
| Protective cover with optional locking |
| Horn |
| Beacon |
| Audible and visual display alarm for excessive slope |
| Code Protected Machine Set Up |
| Hooks for sling loading/lifting |
| Electric Pump |
| Predisposition 230V |
| Operator presence pedal |

Optional equipment

| |
|------------------------------------|
| Onboard generator (5 kVA) |
| 230V power input with differential |
| Predisposition compressed air |
| Predisposition of water |
| Working light |
| Special paint |
| Biodegradable oil |
| Warning Alarm for all movements |
| Warning Travel Alarm |
| Catalytic Converter |
| Spark Arrester and overrun valve |
| Anti Theft code |
| Certificate of verification |
| Safety harness |

