

G45S-7, G50SC-7

Mast type	Maximum Fork Height		Maximum Lowered Height		Fully Extended Height		Free Lift		Rated Load Capacities									
									G45S-7, G50SC-7									
									Tilt Angle				Load Capacities					
									Single Pneu.		Double Pneu		Single Pneu.		Double Pneu			
								FWD	BWD	FWD	BWD	LC 500mm	LC600mm	LC24in	LC500mm	LC600mm	LC24in	
	mm	in	mm	in	mm	in	mm	in	deg	deg	deg	deg	kg	kg	lb	kg	kg	lb
STD	3,000	118	2,230	88	4,420	174	160	6	8	10	8	10	5,000	4,570	10,000	5,000	4,570	10,000
	3,300	130	2,380	94	4,720	186	160	6	8	10	8	10	5,000	4,570	10,000	5,000	4,570	10,000
	3,650	144	2,555	101	5,070	200	160	6	8	10	8	10	5,000	4,570	10,000	5,000	4,570	10,000
	4,000	157	2,880	113	5,420	213	160	6	8	10	8	10	5,000	4,570	10,000	5,000	4,570	10,000
	4,250	167	3,005	118	5,670	223	160	6	8	10	8	10	5,000	4,570	10,000	5,000	4,570	10,000
	4,850	191	3,455	136	6,270	247	160	6	8	5	8	10	4,900	4,480	9,800	4,950	4,525	9,900
FF	3,000	118	2,210	87	4,400	173	860	34	8	10	8	10	5,000	4,575	10,000	5,000	4,575	10,000
	4,000	157	2,090	82	5,415	213	740	29	8	8	8	8	5,000	4,585	10,000	5,000	4,585	10,000
FFT	4,250	167	2,180	86	5,680	224	830	33	8	8	8	8	4,975	4,565	9,950	5,000	4,585	10,000
	4,700	185	2,330	92	6,130	241	980	39	8	8	8	8	4,800	4,400	9,600	4,850	4,450	9,700
	5,150	203	2,480	98	6,580	259	1,130	44	8	3	8	8	4,650	4,265	9,300	4,700	4,310	9,400
	5,600	220	2,630	104	7,030	277	1,280	50	8	3	8	5	4,500	4,125	9,000	4,550	4,175	9,100
	6,050	238	2,780	109	7,480	294	1,430	56	8	3	8	3	3,575	3,280	7,150	4,025	3,690	8,050

G50C-7, G55SC-7

Mast type	Maximum Fork Height		Maximum Lowered Height		Fully Extended Height		Free Lift		Rated Load Capacities									
									G50S-7, G55SC-7									
									Tilt Angle				Load Capacities					
									Single Pneu.		Double Pneu		Single Pneu.		Double Pneu			
								FWD	BWD	FWD	BWD	LC 500mm	LC600mm	LC24in	LC500mm	LC600mm	LC24in	
	mm	in	mm	in	mm	in	mm	in	deg	deg	deg	deg	kg	kg	lb	kg	kg	lb
STD	2,750	108	2,230	88	4,170	164	170	7	8	10	8	10	5,500	5,030	11,000	5,500	5,030	11,000
	3,050	120	2,380	94	4,470	176	170	7	8	10	8	10	5,500	5,030	11,000	5,500	5,030	11,000
	3,400	134	2,555	101	4,820	190	170	7	8	10	8	10	5,500	5,030	11,000	5,500	5,030	11,000
	3,750	148	2,880	113	5,170	204	170	7	8	10	8	10	5,500	5,030	11,000	5,500	5,030	11,000
	4,000	157	3,005	118	5,420	213	170	7	8	10	8	10	5,500	5,030	11,000	5,500	5,030	11,000
	4,600	181	3,455	136	6,020	237	170	7	8	8	8	10	5,500	5,030	11,000	5,500	5,030	11,000
FF	2,875	113	2,210	87	4,275	168	870	34	8	10	8	10	5,500	5,035	11,000	5,500	5,035	11,000
	3,875	153	2,090	82	5,290	208	750	30	8	8	8	8	5,500	5,050	11,000	5,500	5,050	11,000
FFT	4,125	162	2,180	86	5,555	219	840	33	8	8	8	8	5,500	5,050	11,000	5,500	5,050	11,000
	4,575	180	2,330	92	6,005	236	990	39	8	8	8	8	5,375	4,935	10,850	5,425	4,980	10,950
	5,025	198	2,480	98	6,455	254	1,140	45	8	5	8	8	5,200	4,775	10,500	5,150	4,725	10,400
	5,475	216	2,630	104	6,905	272	1,290	51	8	3	8	5	4,650	4,270	9,400	4,750	4,360	9,600
	5,925	233	2,780	109	7,355	290	1,440	57	8	3	8	5	3,625	3,330	7,300	3,525	3,235	7,100

G55C-7

Mast type	Maximum Fork Height		Maximum Lowered Height		Fully Extended Height		Free Lift		Rated Load Capacities							
									G55C-7							
									Tilt Angle				Load Capacities			
									Single Pneu.		Double Pneu		Single Pneu.		Double Pneu	
								FWD	BWD	FWD	BWD	LC 600mm	LC24in	LC600mm	LC24in	
	mm	in	mm	in	mm	in	mm	in	deg	deg	deg	deg	kg	lb	kg	lb
STD	2,750	108	2,230	88	4,170	164	170	7	8	10	8	10	5,500	12,100	5,500	12,100
	3,050	120	2,380	94	4,470	176	170	7	8	10	8	10	5,500	12,100	5,500	12,100
	3,400	134	2,555	101	4,820	190	170	7	8	10	8	10	5,500	12,100	5,500	12,100
	3,750	148	2,880	113	5,170	204	170	7	8	10	8	10	5,500	12,100	5,500	12,100
	4,000	157	3,005	118	5,420	213	170	7	8	10	8	10	5,500	12,100	5,500	12,100
	4,600	181	3,455	136	6,020	237	170	7	8	8	8	10	5,400	11,850	4,900	10,750
FF	2,875	113	2,210	87	4,275	168	870	34	8	10	8	10	5,500	12,100	5,500	12,100
	3,875	153	2,090	82	5,290	208	750	30	8	8	8	8	5,500	12,100	5,500	12,100
FFT	4,125	162	2,180	86	5,555	219	840	33	8	8	8	8	5,500	12,100	5,500	12,100
	4,575	180	2,330	92	6,005	236	990	39	8	8	8	8	5,500	12,100	5,500	12,100
	5,025	198	2,480	98	6,455	254	1,140	45	8	5	8	8	5,150	11,350	4,925	10,850
	5,475	216	2,630	104	6,905	272	1,290	51	8	3	8	5	4,500	9,900	4,575	10,050
	5,925	233	2,780	109	7,355	290	1,440	57	8	3	8	5	3,500	7,700	3,375	7,400



G35S-7 / G40S-7 / G45S-7 / G50C-7 / G55C-7
G40SC-7 / G45SC-7 / G50SC-7 / G55SC-7

7 SERIES FORKLIFTS
Pneumatic LP 3.5 to 5.5 ton capacity



Doosan Industrial Vehicle
Web site : www.doosan-iv.com

2019 Aug

AUTHORIZED DEALER

